

TOWN OF NEWTOWN, CONNECTICUT

INVITATION TO BID

Sealed bids will be received at the office of the Financial Director, 3 Primrose Street, Newtown, Connecticut 06470, until but no later than 11:00 am, Thursday, November 5, 2015:

Cover: 2015/2016 19,500 GVWR 4 X 4 TRUCK

The Purchasing Authority of the Town of Newtown reserves the right to accept or reject any or all options, bids or proposals; to waive any technicality in any bid or part thereof, and to accept any bid deemed to be in the best interest of the Town of Newtown. The Town of Newtown is an Affirmative Action Employer-MBE/WBE are encouraged to bid. Specifications and bid documents may be obtained at [www.newtown-ct.gov](http://www.newtown-ct.gov) under the Purchasing Department.

  
E. Patricia Llodra  
First Selectman

  
Robert G. Tait  
Financial Director

PURCHASING AUTHORITY

**TOWN OF NEWTOWN PURCHASING AUTHORITY**  
**INSTRUCTIONS TO BIDDERS**

1. Submit bids in a sealed envelope plainly marked to identify the particular bid. It is the sole responsibility of the bidder to see that the bid is in the hands of the proper authority prior to the bid opening time. Bidders may be present at the opening of the bids.
2. Withdrawals of, or amendments to bids received later than the time and date specified for bid opening will not be considered.
3. The Purchasing Authority of the Town of Newtown reserves the right to accept or reject any or all options, bids, or proposals; to waive any technicality in any bid, or part thereof, and to accept any bid deemed to be in the best interest of the Town of Newtown, Connecticut.
4. Bids may be held by the Town of Newtown for a period not to exceed sixty (60) days from the opening of the bids for the purpose of reviewing the bids and investigating the qualifications of bidders prior to the awarding of the contract.
5. Bids must be submitted on the "Sealed Bid Request" form enclosed at the end of this packet. All items must be filled in (unit cost, trade-in for each unit, etc.). Failure to comply with this requirement will automatically void the bid.
6. Trade-ins, when indicated, will be listed on the Sealed Bid Request form. The Town of Newtown reserves the right to trade all, some or none of the vehicles listed as deemed in the best interest of the Town. Bidders may submit a bid on the new vehicles with or without trade-ins or may submit bids on the trade-ins only, either individually or by lot. Trade-ins must be detailed individually as indicated on the Sealed Bid Request form. Trade-ins may be used in determining the lowest responsible bid.
7. The Town may consider proximity of the vendor's service as a factor in determining lowest price and reserves the right to award in whole or part to one or more vendors.
8. The Town agrees to pay for all equipment within thirty (30) working days after the equipment has been accepted and claim (invoice) presented.
9. Bid Security when required must be by a **certified check, letter of credit or surety bond** for five percent (5%) of the total bid, payable to the Town of Newtown. If a surety bond is enclosed, it shall be written on AIA Document A310, Bid Bond, unless otherwise provided in the Bidding Documents, and the attorney-in-fact who executes the bond on behalf of the surety shall affix to the bond a certified and current copy of the Power of Attorney.
10. The Town of Newtown reserves the right to retain the bid security of Bidders to whom an award is being considered until either: (a) the Contract has been executed and bonds, if required, have been furnished, or (b) the specified time has elapsed so that Bids may be withdrawn or (c) all bids have been rejected.

11. Prior to awarding any contract exceeding \$25,000.00 for the construction, alteration, or repair for any public building or public work, a 100% performance bond and a labor or materialmen's bond must be furnished by the person to whom the contract is awarded.
12. Performance Bond when required must be by a **certified check, letter of credit or performance bond** for one hundred percent (100%) of the total bid. When submitting a performance bond, bonds must be written on AIA Document A312, Performance Bond and Payment Bond. Both bonds shall be written in the amount of the Contract Sum.
13. The successful bidder will be required to post a Certificate of Insurance, with the Town of Newtown named as additional insured, in an amount to be determined by the Town of Newtown.

**1 (ONE)2015 or 2016 Base Bare Chassis (No Body Equipment), 4X4 WITH 19,500 GVWR**

**Bid Specifications**

**CIRCLE ONE COMPLY: Y=YES N=NO**

**Description**

<b>FRAME RAILS:</b>	High Strength Low Alloy Steel (80,000 PSI Yield); 7.375" x 3.079" x .312" (187.45mm x 78.2mm x 8.0mm) With Transition to 9.125" x 3.079" x .312" (231.8mm x 78.2mm x 8.0mm); Includes 1.2" (30mm) Drop Under Cab; 335.2" (8512.2mm) Maximum OAL	Y / N
<b>TOW HOOK, FRONT:</b>	(2) Frame Mounted	Y / N
<b>RATING/CAPABILITY:</b>	GVWR: 19500. Calc. GVWR:19500 Calc. Start/Grade Ability: 37.23%/2.30% @ 55 MPH Calc. Geared Speed: 99.9 MPH	Y / N Y / N Y / N
<b>DIMENSION:</b>	Wheelbase: 158.00, CA: 83.60, Axle to Frame: 63.00	Y / N
<b>ENGINE, DIESEL:</b>	(MaxxForce 7) EPA 2010, 300HP @ 2600 RPM, 660 lb-ft Torque @ 1600 RPM, 2800 RPM, Governed Speed, 300 Peak HP (Max)	Y / N
<b>TRANSMISSION AUTOMATIC:</b>	(Allison 1350_RDS) 5 <sup>th</sup> Generation Controls: Close Ratio, 6-Speed, with Overdrive; with PTO Provision, Includes Park Pawl, Less Retarder, with 19,500-lb GVW & 30,000-lb GCW Max. on/off hwy	Y / N
<b>AXLE, FRONT DRIVING:</b>	(Dana Spicer 70-273) Single Reduction, 8,000-lb Capacity	Y / N
<b>AXLE, REAR, SINGLE:</b>	(Dana Spicer S110) Single Reduction, With Offset Housing; 13,500-lb Capacity, 160 Wheel Ends, Gear Ratio: 4.30	Y / N
<b>CAB:</b>	Conventional	Y / N
<b>TIRE, FRONT:</b>	(2) 225/70R19.5 G622 RSD (GOODYEAR) 641 Rev/Mile, load range G, 14 ply	Y / N
<b>TIRE, REAR:</b>	(4) 225/70R19.5 G622 RSD (GOODYEAR) 641 rev/mile, load range G, 14 ply	Y / N
<b>SUSPENSION, RR, SPRING, SINGLE:</b>	Vari-Rate; 13,500-lb Capacity	Y / N
<b>PAINT:</b>	Forest Green Metallic (Prem)	Y / N
<b>LICENSE PLATE HOLDER:</b>	Includes Upper & Lower Mounting Plate Hardware, Mounted in Existing Holes in Front Bumper	Y / N

**CIRCLE ONE COMPLY: Y=YES N=NO**

<b>BUMPER, FRONT:</b>	Full Width, Aerodynamic, Steel, Chrome Plated, 0.118" Material Thickness	Y / N
<b>WHEELBASE RANGE:</b>	128" (325cm) Through and Including 183" (465cm)	Y / N
<b>AXLE, FRONT DRIVING:</b>	(Dana Spicer 70-273) Single Reduction, 8,000-lb Capacity	Y / N
<b>AXLE, FRONT DRIVING, LUBE:</b>	(EmGard 75W-90) Synthetic Oil; 1 thru 29.99 Pints	Y / N
<b>SUSPENSION, FRONT, SPRING:</b>	Taper Leaf, Shackle Type; 8,000-lb Capacity; With 7,000-lb Capacity Rubber Auxiliary Spring (1000-lb Capacity), With Shock Absorbers	Y / N
<b>BRAKE SYSTEM, HYDRAULIC:</b>	(TRW 355) Split System, With Three Channel ABS	Y / N
<b>BRAKE LININGS, FRONT:</b>	Hx-73, Non-Asbestos	Y / N
<b>BRAKE LININGS, REAR:</b>	HX-73, Non-Asbestos	Y / N
<b>BRAKE, PARKING:</b>	Drum-in-Hat Type; for Hydraulic Brake Chassis; Activated by Lever in Cab; Mounted in Rear Wheels	Y / N
<b>PARKING BREAK CONTROL:</b>	Lever, Floor Mounted, Located Right of Driver	Y / N
<b>BRAKES, FRONT:</b>	HYDRAULIC DISC (TRW) 15.35" X 1.54" Rotors; Dual 2.36" (60mm) Diam. Pistons	Y / N
<b>BRAKES, REAR:</b>	HYDRAULIC DISC (TRW) 15.35" X 1.54" Rotors; Dual 2.36" (60mm) Diam. Pistons	Y / N
<b>STEERING COLUMN:</b>	Tilting and Telescoping	Y / N
<b>STEERING WHEEL:</b>	2-Spoke, 18" Diam., Black	Y / N
<b>STEERING GEAR:</b>	(Sheppard MD83) Power	Y / N
<b>EXHAUST SYSTEM:</b>	Single, Horizontal, Aftertreatment Device Frame Mounted Left Side Back of Cab; Includes Horizontal Tail Pipe	Y / N
<b>ENGINE EXHAUST BRAKE:</b>	For MaxxFORCE 7 V8 Engines, Electronically Activated	Y / N
<b>ELECTRICAL SYSTEM:</b>	12-Volt, Standard Equipment	Y / N
<b>BATTERY BOX:</b>	Steel	Y / N
<b>DATA LINK CONNECTOR:</b>	For Vehicle Programming and Diagnostics In Cab	Y / N
<b>FUSES ELECTRICAL:</b>	SAE Blade-Type	Y / N
<b>HAZARD SWITCH:</b>	Push On/Push Off, Located on Top of Steering Column Cover	Y / N
<b>HEADLIGHT DIMMER SWITCH:</b>	Integral with Turn Signal Lever	Y / N
<b>HEADLIGHTS:</b>	(2) Sealed Beam Halogen, 5" x 7" Rectangular, with Molded-In Argent Colored Bezels	Y / N
<b>HORN:</b>	ELECTRIC, Dual	Y / N
<b>JUMP START STUD:</b>	Located on Positive Terminal of Outermost Battery	Y / N
<b>PARKING LIGHT:</b>	Integral with Front Turn Signal and Rear Tail Light	Y / N
<b>RUNNING LIGHT:</b>	(2) Daytime, Included with Headlights	Y / N
<b>STARTER SWITCH:</b>	Electric, Key Operated	Y / N
<b>STOP, TURN, TAIL &amp; B/U LIGHTS:</b>	Dual, Rear, Combination with Reflector	Y / N

CIRCLE ONE COMPLY: Y=YES N=NO

<b>TURN SIGNAL SWITCH:</b>	Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature	Y / N
<b>TURN SIGNALS, FRONT:</b>	Includes Reflectors and Solid State Flashers; Flush Mounted	Y / N
<b>WINDSHIELD WIPER SWITCH:</b>	2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever	Y / N
<b>WINDSHIELD WIPERS:</b>	Single Motor, Electric, Cowl Mounted	Y / N
<b>WIRING, CHASSIS:</b>	Color Coded and Continuously Numbered	Y / N
<b>CIGAR LIGHTER:</b>	includes Ash Cup	Y / N
<b>POWER SOURCE:</b>	Cigar Type Receptacle without Plug and Cord	Y / N
<b>ALTERNATOR:</b>	(Leece-Neville AVI160P2013) Brush Type; 12 Volt 160 Amp. Capacity, Pad Mount, With Remote Sense	Y / N
<b>BODY BUILDER WIRING:</b>	Back of Standard Cab at Left Frame or Under Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/Backup/Accessory Power/Ground and sealed Connector for Stop/Turn	Y / N
<b>ELEC. TRAILER BRAKE/LIGHTS:</b>	Accommodation Package to Rear of Frame; for Combined Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package With Cab Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket.	Y / N
<b>BATTERY SYSTEM:</b>	Maintenance-Free (3) 12-Volt 2250CCA Total	Y / N
<b>RADIO:</b>	AM/FM/WB/Clock/Bluetooth/USB Input/3MM Auxillary Input, MP3, Bluetooth for Phone & Music, With Multiple Speakers	Y / N
<b>BACK-UP ALARM:</b>	Electric, 102 dBA	Y / N
<b>AUXILIARY HARNESS:</b>	3.0' for Auxiliary Front Head Lights and Turn Signals for Front Plow Applications	Y / N
<b>JUMP START STUD:</b>	Remote Mounted	Y / N
<b>WIPER SPD CONTROL:</b>	Force Wipers to slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time	Y / N
<b>CLEARANCE/MARKER LIGHTS:</b>	(5) Amber LED Lights, Flush Mounted on Cab or Sunshade	Y / N
<b>TEST EXTERIOR LIGHTS:</b>	Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights	Y / N
<b>INDICATOR, COOLANT LEVEL:</b>	With Audible Alarm	Y / N
<b>HEADLIGHT WARNING BUZZER:</b>	Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position	Y / N

**CIRCLE ONE COMPLY: Y=YES N=NO**

<b>STARTING MOTOR:</b>	(Delco Remy 29MT) 12 Volt; Less Thermal Over-Crank Protection, With Integrated Magnetic Switch	Y / N
<b>CIRCUIT BREAKERS:</b>	Manual-Reset (Main Panel) SAE Type III With Trip Indicators, Replaces All Fuses Except For 5-Amp Fuses	Y / N
<b>FOG LIGHTS:</b>	(2) (Grote) Clear, Halogen, Rectangular	Y / N
<b>GRILLE:</b>	Chrome, with Chrome Headlight Bezels	Y / N
<b>FRONT END:</b>	Tilting, Fiberglass, With Three Piece Construction	Y / N
<b>HOOD TILT ASSIST:</b>	Includes Torsion Bar Spring System	Y / N
<b>PAINT SCHEMATIC:</b>	Single Color	Y / N
<b>TOOL KIT:</b>	Rim Wrench and Handle Only	Y / N
<b>PAINT TYPE:</b>	Base Coat/Clear Coat, 1-2 Tone	Y / N
<b>PAINT CLASS:</b>	Premium Color	Y / N
<b>CLUTCH:</b>	Omit Item (Clutch & Control)	Y / N
<b>BLOCK HEATER, ENGINE:</b>	(Phillips) 120 Volt/1000 Watt	
<b>BLOCK HEATER SOCKET:</b>	Receptacle Type; Mounted below Drivers Door	Y / N
<b>ENGINE, DIESEL:</b>	(MaxxForce 7) EPA 2010, 300 HP @ 2600 RPM, 660 lb-ft Torque @ 1600 RPM, 2800 RPM Governed Speed, 300 Peak HP (Max)	Y / N
<b>ANTI-FREEZE:</b>	Red Extended Life Coolant; -40 Degrees F/ -40 Degrees C; for MaxxForce and Navistar Engines	Y / N
<b>CRUISE CONTROL:</b>	Electronic; Controls Integral to Steering Wheel	Y / N
<b>ENGINE OIL DRAIN PLUG:</b>	Magnetic	Y / N
<b>ENGINE SHUTDOWN:</b>	Electric, Key Operated	Y / N
<b>FUEL FILTER:</b>	Engine Mounted	Y / N
<b>FUEL HEATER:</b>	Included with Fuel/Water Separator	Y / N
<b>FUEL/WATER SEPERATOR:</b>	Engine Mounted	Y / N
<b>GLOW PLUG:</b>	Automatic with Indicator light	Y / N
<b>GOVERNOR:</b>	Electronic	Y / N
<b>OIL FILTER, ENGINE:</b>	Drop-In Cartridge Type	Y / N
<b>FAN DRIVE:</b>	(Borg-Warner Series 790) Viscous Type, Screw On	Y / N
<b>FAN:</b>	Nylon	Y / N
<b>RADIATOR:</b>	Aluminum; 2-Row, Cross Flow, Side-by-Side System, 697 SqIn Louvered, With 225 SqIn CAC, With In-Tank Oil Cooler	Y / N
<b>DEAERATION SYSTEM:</b>	Including Surge Tank	Y / N
<b>HOSE CLAMPS:</b>	Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps	Y / N
<b>RADIATOR HOSES:</b>	Premium, Rubber	Y / N

CIRCLE ONE COMPLY: Y=YES N=NO

<b>FEDERAL EMISSIONS:</b>	EPA, OBD AND GHG Certified for Calendar Year 2014	Y / N
<b>AIR CLEANER:</b>	With Service Protection Element	Y / N
<b>AIR CLEANER RESTRICTION:</b>	Air Cleaner Mounted restriction gauge	Y / N
<b>THROTTLE, HAND CONTROL:</b>	Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel	Y / N
<b>ENGINE CONTROL:</b>	Remote mounted Provision for; Includes Wiring for Body Builder Installation of PTO Controls; With Ignition Switch Control for MaxxForce and Navistar post 2007 Emissions Electronic Engines	Y / N
<b>FAN DRIVE SPECIAL EFFECTS:</b>	Fan Cooling Ring with Fan Shroud Effects, Engine Mounted	Y / N
<b>EMISSION COMPLIANCE:</b>	Federal, Does Not Comply With California Clean Air Idle Regulations	Y / N
<b>TRANSMISSION:</b>	AUTOMATIC (Allison 1350_RDS) 5 <sup>th</sup> Generation Controls; Close Ratio, 6-Speed, with Overdrive; with PTO Provision, Includes Park Pawl, Less Retarder, with 19,500-lb GVW & 30,000-lb GCW Max. on/off hwy	Y / N
<b>TRANSFER CASE:</b>	(Fabco TC-28) Two-Speed, Gear Drive, 3,600 lb-ft Capacity with Electronic Shifting Controls, without PTO Provision	Y / N
<b>TRANSFER CASE LUBE:</b>	(EmGard 50W) Synthetic; 1 thru 14.99 Pints	Y / N
<b>WIRING, BODY BUILDER:</b>	Installed Wiring for Transmission/PTO Controls, for Allison 1000, 2000, 2100, 2200, 2400, 2500 Series Transmission	Y / N
<b>TRANSMISSION OIL:</b>	Synthetic; 20 thru 28 Pints	Y / N
<b>ALLISON INPUT/OUTPUT:</b>	Spare for Rugged Duty Series (RDS), 305/354 Includes J1939 Based Auto Neutral	Y / N
<b>TRANS TCM LOCATION:</b>	Located Inside Cab	Y / N
<b>SHIFT CONTROL PARAMETERS:</b>	Allison Load Based Shift Schedules (LBSS)	Y / N
<b>AXLE, REAR, SINGLE:</b>	(Dana Spicer S110) Single Reduction, With Offset Housing; 13,500-lb Capacity, 160 Wheel Ends. Gear Ratio: 4.30	Y / N
<b>REAR AXLE DRAIN PLUG:</b>	(1) MAGNETIC, For Single Rear Axle	Y / N
<b>SUSPENSION, RR, SPRING:</b>	Vari-Rate; 13,500-lb Capacity	Y / N
<b>AXLE, REAR,LUBE:</b>	(EmGard 75W-90) Synthetic Oil; 1 thru 29.99 pints	Y / N
<b>FUEL TANK:</b>	Top Draw; Rectangular, Steel; 15" Tank Depth, 40 U.S. Gal., 151 L Capacity, Includes Fuel Filler Assembly and Vent Hosing, Mounted Between Frame Sidemembers and Behind Rear Axle	Y / N
<b>FLOOR COVERING:</b>	Transmission Cover, Floor Mats and Seal	Y / N
<b>CAB:</b>	Conventional	Y / N
<b>ARM REST:</b>	(2) Molded Plastic; One Each Door	Y / N
<b>CLEARANCE/MARKER LIGHTS:</b>	(5) Flush Mounted	Y / N
<b>COAT HOOK, CAB:</b>	Located on Rear Wall, Centered Above Rear Window	Y / N
<b>CUP HOLDERS:</b>	Two Cup Holders, Located in Lower center of Instrument Panel	Y / N

**CIRCLE ONE COMPLY: Y=YES N=NO**

<b>DOME LIGHT, CAB:</b>	Rectangular, Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Console, Center Mounted	Y / N
<b>GLASS, ALL WINDOWS:</b>	Tinted	Y / N
<b>GRAB HANDLE, CAB INTERIOR:</b>	(1) "A" Pillar Mounted, Passenger Side	Y / N
<b>GRAB HANDLE, CAB INTERIOR:</b>	(2) Front of "B" Pillar Mounted, One Each Side	Y / N
<b>INTERIOR SHEET METAL:</b>	Upper Door (Above Window Ledge) Painted Exterior Color	Y / N
<b>STEP:</b>	Two Steps Per Door	Y / N
<b>HEATER SHUT-OFF VALVES:</b>	(2) Ball Check valve Type	Y / N
<b>GAUGE CLUSTER:</b>	English With English Electronic Speedometer	Y / N
<b>GAUGE CLUSTER:</b>	(5) Engine Oil Pressure (Electronic), Water Temperature (Electronic), Fuel (Electronic), Tachometer (Electronic), Voltmeter	Y / N
<b>ODOMETER DISPLAY:</b>	Miles, Trip Miles, Engine Hours, Trip Hours, Fault Code Readout	
<b>WARNING SYSTEM:</b>	Low Fuel, Low Oil Pressure, High Engine Coolant Temp, and Low Battery Voltage (Visual and Audible)	Y / N
<b>GAUGE, AUTO TRANS:</b>	Oil temp for Allison Transmission	Y / N
<b>GAUGE, AIR CLEANER:</b>	(Filter-Minder) With Black Bezel Mounted in Instrument Panel	Y / N
<b>IP CLUSTER DISPLAY:</b>	On Board Diagnostics Display of Fault Codes in Gauge Cluster	Y / N
<b>SEAT, DRIVER</b>	(National 2000) Self Contained with Compressor, Mid Back, Vinyl, Less Isolator, Less Lumbar, 2 Position Front Cushion Adjust, -3 to + 14 Degree Seat Back Adjust	Y / N
<b>SEAT BELT:</b>	3-Point, Lap and Shoulder Belt Type	Y / N
<b>SEAT, TWO-MAN PASSENGER:</b>	(National) Vinyl, With Under Seat Storage Compartment	Y / N
<b>GRAB HANDLE:</b>	(2) Chrome Towel Bar Type With Anti-Slip Rubber Inserts: for Cab Entry, Mounted Left and Right, Each Side at "B" Pillar	Y / N
<b>MIRRORS:</b>	(2) (Lang Mekra) Styled; Rectangular, Power Both Sides, Thermostatically Controlled Heated, Clearance Lights LED, Bright Finish Heads & Brackets, Breakaway Type, 7.09" x 15.75" Integral Convex Both Sides	Y / N
<b>AIR CONDITIONER:</b>	(Blend-Air) With Integral Heater & Defroster	Y / N
<b>HEATER HOSES:</b>	Premium	Y / N
<b>HOSE CLAMPS, HEATER HOSE:</b>	Mubea Constant Tension Clamps	Y / N
<b>REFRIGERANT:</b>	Hydrofluorocarbon HFC-134A	Y / N
<b>INSTRUMENT PANEL:</b>	Center Section, Flat Panel	Y / N
<b>WINDOW,POWER:</b>	(2) and Power Doors Locks Left and Right Doors, Express Down Feature	Y / N
<b>HVAC FRESH AIR FILTER:</b>	Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood	Y / N
<b>CAB INTERIOR TRIM:</b>	"A" PILLAR COVER Molded Plastic	Y / N

**CIRCLE ONE COMPLY: Y=YES N=NO**

<b>CAB INTERIOR TRIM PANELS:</b>	Cloth Covered Molded Plastic, Full Height; All Exposed Interior Sheet Metal is Covered Except for the Following: with a Two-Man Passenger Seat or with a Full Bench Seat the Back Panel is Completely Void of Covering	Y / N
<b>CAB SOUND INSULATION:</b>	Includes Dash and Engine Cover Insulators	Y / N
<b>CONSOLE OVERHEAD:</b>	Molded Plastic; With Dual Storage Pockets with Retainer Nets, CB Radio Pocket, Speakers, and Reading Lights	Y / N
<b>COURTESY LIGHT:</b>	(2) Mounted In Front Map Pocket Left and Right Side	Y / N
<b>DOOR TRIM PANELS:</b>	With Cloth Inset on Bolster Driver and Passenger Doors	Y / N
<b>FLOOR COVERING:</b>	Rubber, Black	Y / N
<b>GAUGE, TEMPERATURE:</b>	Ambient temperature Includes Wiring and Sensor With Display Unit Mounted in Cluster	Y / N
<b>HEADLINER:</b>	Soft Padded Cloth	Y / N
<b>INSTRUMENT PANEL TRIM:</b>	Molded Plastic with Black Center Section	Y / N
<b>STORAGE POCKET, DOOR:</b>	(2) Molded Plastic (Carpet Texture), Full-Length; Driver and Passenger Doors	Y / N
<b>SUN VISOR:</b>	(3) Padded Vinyl: 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Vanity Mirror and Ticket Strap, Plus 1 Auxiliary Visor (Front Only), Driver Side	Y / N
<b>LOW WASHER INDICATOR:</b>	Dash mounted, illuminated	Y / N
<b>MODESTY PANEL:</b>	Painted	Y / N
<b>SUNSHADE, EXTERIOR:</b>	Aerodynamic, Painted Roof Color; Includes Integral Clearance/Marker Lights	Y / N
<b>WHEELS, FRONT DISC:</b>	19.5" Polished Aluminum; 10-Stud (225MM BC) Hub Piloted, Flanged Nut, Metric mount, 6.00 DC Rims; With Steel Hubs	Y / N
<b>WHEEL SEALS, FRONT:</b>	(Chicago Rawhide Nitrile) for Oil Lubricated Wheel Bearings	Y / N
<b>UPFITTER SWITCHES:</b>	(3) Latched Rocker Switches, (1) PTO Switch, (2) Generic Switches to Control (3) 30 amp relays, with Programmable Interlocks, for Body Builder Hook up in the Engine Compartment Left Side, Recommended for Automatic Transmissions	Y / N
<b>(2) TIRE, FRONT:</b>	225/70R19.5 G622 RSD (GOODYEAR) 641 rev/mile, load range G, 14 ply	Y / N
<b>(4) TIRE, REAR:</b>	225/70R19.5 G622 RSD (GOODYEAR) 641 rev/mile, load range G, 14 ply	Y / N

**Services Section:**

**CIRCLE ONE COMPLY: Y=YES N=NO**

**Description**

**WARRANTY:** Standard 36 Month/36,000 Miles **Y / N**

**SRV CONTRACT, EXT ENGINE:** To 60-Month/100,000 Miles (160,000 km), 3600 Hours; Includes Engine, Engine Electronics, and Injectors; for MaxxForce 7 Engines **Y / N**

**Delivery:** Truck shall be delivered to Newtown Parks and Recreation or a body vendor Within 100 miles as required with minimum ½ tank of fuel. Factory PDI will be done prior to body & equipment being installed. Truck will be clean inside and outside and all fluids will be at proper levels. (2) keys, the owners & warranty manuals, and factory window sticker will be provided at delivery. Chassis to be delivered within 45 days of bid award **Y / N**

Bid submittal- shall include a printed quotation stating standard equipment and all optional equipment.

Bid price including all specified equipment \$ \_\_\_\_\_

**TRADE IN:**

2003 Chevrolet 2500 HD with 8' Western plow, approximately

90,000 miles.

Allowance: \$ \_\_\_\_\_

Net Cash Price: \$ \_\_\_\_\_

Exceptions: \_\_\_\_\_

---

---

---

---

Bidder name: \_\_\_\_\_

Bidder address: \_\_\_\_\_

Bidder phone #: \_\_\_\_\_

Bidder fax #: \_\_\_\_\_

Bidder FEIN #: \_\_\_\_\_

Bid submitted by: \_\_\_\_\_

Title: \_\_\_\_\_

e- mail address: \_\_\_\_\_

Date: \_\_\_\_\_

Signature: \_\_\_\_\_